

| 9-6 | |
|-----|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

Truck

E н

RAISE YOUR STANDARDS

| External Cleat Height Sleeve Exborned Sleeve | ▲ Overall Height |
|---|--------------------------------------|

Continental Series Flagpole 35' Anodized Clear Flagpole with External Truck

| SPECIFICATIONS | | | |
|----------------------------|-------------------|--|--|
| Continental Series | | | |
| SKU | 206110 | | |
| Finish | Anodized Clear | | |
| Exposed Height | 35 ft | | |
| Overall Height | 38.5 ft | | |
| Top Diameter | 3.5 in | | |
| Bottom Diameter | 6 in | | |
| Wall Thickness | 0.188 in | | |
| Shipping | 229 lbs | | |
| Max Windspeed | 145 mph | | |
| Max Windspeed With Flag | 97 mph | | |
| Recommended Flag Size | 6' x 10' | | |

Meets ASTM: B 241 - Standard Specification for Aluminum and Aluminum-Alloy Seamless Pipe and Seamless Extruded Tube. B 597 - Standard Practice for Heat Treatment of Aluminum Alloys.

Meets NAAMM: FP 1001 - Guide Specifications for Design of Metal Flagpoles.